



CLIMA-SEAL

General description

- Acrylic water based sealant
- Available in 6 kg buckets or 280 ml cartridges
- Excellent adhesion to metal
- Durability and flexibility
- Use : airtightness on airduct



Technical specifications

BASE MATERIAL	Water based acrylic polymer
ASPECT	Malleable paste
COLOR	Grey
WEIGHT PER LITER	1,60 Kg
APPLICATION TEMPERATURE	+5°C / +40°C
OPERATING TEMPERATURE	-30 ° C / +95 ° C
DRYING TIME	Touch : 30 minutes
	Through : 4 to 6 days
REACTION TO FIRE	Wet : non flammable
	British standard : BS 476 / Part 7 class 1
	French standard : M1

Application

Application by brush or spatula on clean, dry and non-greasy surfaces and a temperature of +5 °C to +40 °C.
Read the Material Safety Datasheet

Storage

At least 12 months when stored in a dry place at temperatures between +5 °C and +30 °C in its original packaging.
Protect from frost.



NEU 6000, S.A.

Pol. Ind. "La Torre"
Av. Joaquim de Barnola i Bassols, 6
08760 Martorell - Barcelona
SPAIN

T. +34 93 774 57 09
F. +34 93 774 18 33
neu@rami-system.es
www.rami-system.es