

GSP-SS

General description

The perforated base hangers are designed to fix efficiently insulation concrete and any other rough surfaces.


It consists of a pin, firmly mounted on a perforated base.

Locking washers supplied in each box.



Technical description

Base	Material	Stainless steel AISI 304
	Dimensions	50 x 50 mm (2" x 2")
	Thickness	0,4 mm (28 ga.)
	Perforation	44 holes, dia. 3,3 mm
Shank	Material	Stainless steel AISI 304
	Diameter	2,7 mm (12 ga.)
	Lengths	19 to 400 mm (3/4" to 16")




Locking washer : CL 2-30-SS	Material	Stainless steel spring type AISI 304
	Diameter	30 mm (1 3/16")
	Thickness	0,33 mm (29 ga.)
	Edges	Bevelled




Storage

Store in a dry place


Application




Apply adequate adhesive to the underside of the hanger, or use rivets or screws.



Position the hanger and press until the adhesive seeps through perforations.



As soon as the strength of adherence is sufficient, impale the insulation on the hangers. Please consult your glue supplier to know about the drying time.



Secure with CL locking washers. If necessary cover the point with a protective cap.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.06.20



NEU 6000, S.A.

Pol. Ind. "La Torre"
Av. Joaquim de Barnola i Bassols, 6
08760 Martorell - Barcelona
SPAIN

T. +34 93 774 57 09
F. +34 93 774 18 33
neu@rami-system.es
www.rami-system.es