



TECHNICAL DATA SHEET FLAT ACCESS DOOR

| <u> </u> | |
|---|--|
| RAMI-SYSTEM® IDENTIFICATION CODE | 5R394XXX |
| PRODUCT NAME | GALVANIZED FLAT ACCESS DOOR |
| PRODUCT DESCRIPTION | FAD-XX |
| PRODUCT'S APPLICATION FIELD | METAL SHEET RECTANGULAR DUCTS |
| MATERIAL SPECIFICATION | GALVANIZED STEEL DX51+Z275 MAC |
| THICKNESS (mm) | 0,8 - 1,0 - 1,2 |
| No. OF SIZES ACCORDING TO DUCT DIMENSION | 7 |
| GASKET SEAL (mm) | CLOSED CELL POLYETHYLENE 15 x 6 |
| TIGHTENING THROUGH 2 BLUE POLYAMIDE KNOBS | ON M-8 / M-10 THREADED BARS |
| TEMPERATURE WORK RANGE | -40° C / +90° C |
| EASY ASSEMBLY: | USING A SELF-ADHESIVE TEMPLATE |
| 1ST STICK TEMPLATE ON THE DUCT | 2 ND CUT HOLE FOLLOWING ITS CONTOUR |
| 3RD LOOSEN THE KNOBS OF THE ACCESS DOOR | 4TH PLACE IT IN THE HOLE AT AN ANGLE AND TIGHTEN |



| SIZES CK. HEIGHT | Α | В | С |
|---------------------|-----|-----|-----|
| 180×80 | 81 | 184 | 103 |
| 0,8 8 | 110 | 210 | 100 |
| 200×100 | 100 | 200 | 103 |
| 8 8,0 | 117 | 219 | 105 |
| 250×150 | 152 | 242 | 90 |
| 8 8,0 | 183 | 272 | 89 |
| 300×200 | 200 | 300 | 100 |
| 0,8 8,0 | 230 | 330 | 100 |
| 100×300 | 300 | 382 | 82 |
| 1,0 10 | 332 | 412 | 87 |
| 500×400 | 400 | 500 | 100 |
| ,2 9 | 433 | 530 | 97 |
| 00×450 | 448 | 602 | 154 |
| 1,2 14 | 480 | 628 | 148 |



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.



NEU 6000, S.A.

Pol. Ind. "La Torre" Av. Joaquim de Barnola i Bassols, 6 08760 Martorell - Barcelona SPAIN