


TECHNICAL DATA SHEET FLAT ACCESS DOOR INSULATED + TRAY

1	
RAMI-SYSTEM® IDENTIFICATION CODE	1Y111XXX
PRODUCT NAME	INSULATED ACCESS DOOR + TRAY
2 TYPES OF TRAY	OF 20 mm OR 40 mm
PRODUCT'S APPLICATION FIELD	DOUBLE RECT. DUCTS OR INSULATED PANELS
MATERIAL SPECIFICATION	GALVANIZED STEEL DX51+Z275 MAC
THICKNESS (mm)	0,8 - 1,0 - 1,2
No. OF SIZES ACCORDING TO DUCT DIMENSION	7
GASKET SEAL (mm)	CLOSED CELL POLYETHYLENE 6 mm
TIGHTENING THROUGH 2 BLUE POLYAMIDE KNOBS	ON M-8 / M-10 THREADED BARS
TEMPERATURE WORK RANGE	-40° C / +90° C
EASY ASSEMBLY:	USING A SELF-ADHESIVE TEMPLATE
1ST STICK TEMPLATE ON THE INSIDE DUCT	2 ND CUT HOLE FOLLOWING ITS CONTOUR
3RD FIX TRAY USING THE 2 DRILL HOLES	4 [™] PLACE ACCESS DOOR AND TIGHTEN



SIZES ICK. HEIGHT	Α	В	С
180×80	81	184	103
0,8 8	110	210	100
200×100	100	200	103
8 8,0	117	219	105
250×150	152	242	90
8 8,0	183	272	89
300×200	200	300	100
0,8 8,0	230	330	100
400×300	300	382	82
1,0 10	332	412	87
500×400	400	500	100
1,2 9	433	530	97
600×450	448	602	154
1,2 14	480	628	148



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.



NEU 6000, S.A.

Pol. Ind. "La Torre" Av. Joaquim de Barnola i Bassols, 6 08760 Martorell - Barcelona SPAIN