



## TECHNICAL DATA SHEET RUBBER JOINT OPENING PROTECTION

RAMI-SYSTEM® IDENTIFICATION CODE	2J00500X
PRODUCT NAME	RUBBER JOINT DUCT OPENINGS PROTECTION
PRODUCT DESCRIPTION	RUBBER JOINT PROTECT
CHARACTERISTICS OF SPOTS TO PROTECT	OPENINGS ON METAL DUCTS
PRODUCT'S APPLICATION FIELD	CIRCULAR AND RECTANGULAR METAL DUCT
MATERIAL SPECIFICATIONS	FIREPROOF RUBBER
RUBBER JOINT FOR PROTECTION	RUBBER JOINT M-1 BLACK COLOR
DENSITY / HARDNESS SHORE "A"	1,43 gr/cm <sup>3</sup> / 63
AIRTIGHTNESS LEVEL	CLASS C
TEMPERATURE WORK RANGE	-20° C / +80° C
ADHESIVE TYPE	PERMANENT ADHESIVE HOT MELT
ASSEMBLY CHARACTERISTICS	EASY AND FAST WITH NO NEED OF TOOLS
JOINT CHARACTERISTICS	PERFECT INSIDE ADAPTATION, EXCELLENT FINISH



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.



**NEU 6000, S.A.**

Pol. Ind. "La Torre"  
Av. Joaquim de Barnola i Bassols, 6  
08760 Martorell - Barcelona  
SPAIN

T. +34 93 774 57 09  
F. +34 93 774 18 33  
neu@rami-system.es  
www.rami-system.es