

# StrutFoot

Universal Flat Roof Support System



StrutFoot 4 system shown



**Designed & Manufactured in the UK**

- UNISTRUT® Framework provides strength & convenience for cable management installation
- Cross compatibility with all Unistrut type brackets
- Fast & economical systems for mounting M&E services, Air Conditioning & Refrigeration on flat roofs
- Easy to install for individual products or complete installations
- No penetration of waterproof roof membrane
- Standard & bespoke configurations
- Anti-Vibration pads pre attached to feet
- Feet & blocks available separately



StrutFoot Complete Leg Assembly



StrutFoot 2 system



StrutFoot 4 system



StrutFoot 6 system

## StrutFoot Support System - Technical Information

Part No.	Complete leg assembly supplied	Sliding arms supplied	Steel frame side rails (mm)	Steel frame sliding arms (mm)	Overall Max. width (mm) with feet	Overall Min. width (mm) with feet	Product weight (Kg)	Max S.W.L (Kg)
StrutFoot2	4	2	1000	1300	1670	1450	32	700
StrutFoot4	6	4	2000	1300	1670	1450	54	1050
StrutFoot6	8	6	3000	1300	1670	1450	78	1400
StrutFoot8	10	8	4000	1300	1670	1450	101	1750
StrutFoot10	12	10	5000	1300	1670	1450	124	2100
StrutFoot12	14	12	6000	1300	1670	1450	148	2450

Welding to BS287-1 Galvanising to BS EN ISO 1461:1999  
 ISO 9001 Quality & ISO 14001 Environmental Certification Number 1753