

GSP

General description


The perforated base hangers are designed to fix efficiently insulation on concrete and any other rough surfaces.

It consists of a pin, firmly mounted on a perforated base.

Locking washers supplied in each box.

Technical description

| | | |
|--------------|-------------|---|
| Base | Material | Galvanized steel |
| | Dimensions | 50 x 50 mm (2" x 2") |
| | Thickness | 0,4 mm (28 ga.) |
| | Perforation | 44 holes, dia. 3.3 mm |
| Shank | Material | 63 mm length ≤ galvanized steel 76 mm length ≥ copper plated steel |
| | Diameter | 2,7 mm (12 ga.) |
| | Lengths | 19 to 400 mm (3/4" to 16") |
| | | |




| | | |
|-------------------------------------|-----------|-------------------------|
| Locking washer : CL 2-30 | Material | Galvanized spring steel |
| | Diameter | 30 mm (1 3/16") |
| | Thickness | 0,35 mm (28 ga.) |
| | Edges | Bevelled |




Storage

Store in a dry place.


Application




Apply adequate adhesive to the underside of the hanger, or use rivets or screws.



Position the hanger and press until the adhesive seeps through perforations.



As soon as the strength of adherence is sufficient, impale the insulation on the hangers. Please consult your glue supplier to know about the drying time.



Secure with CL locking washers. If necessary cover the point with a protective cap.

Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.06.20



NEU 6000, S.A.

Pol. Ind. "La Torre"
Av. Joaquim de Barnola i Bassols, 6
08760 Martorell - Barcelona
SPAIN

T. +34 93 774 57 09
F. +34 93 774 18 33
neu@rami-system.es
www.rami-system.es